## **WOOD STAINS**



POLYURETHANE SPECIALISTS SINCE 1979

- Antique Brown
- Black
- Espresso
- Jarrah
- Mahogany
- Oak

- Red
- Teak Brown
- Teak Gold
- Walnut
- Reducer /
  Extender







URETHANE COATINGS WOOD STAINS are suitable for all timber structures including; flooring, steps, furniture, door jambs, window frames, architraves, mouldings and railings.

WOOD STAINS have been developed to add colour and enhance the grain patterns and natural contours of all timber, parquetry and particle board.

> URETHANE COATINGS A DIVISION OF ERA POLYMERS PTY LTD Call Us - Tel: (02) 9666 3888 www.urethanecoatings.com.au

## **URETHANE** COATINGS



Wood Stains have varying drying times depending on the application method. When applied with the "Rag on, Rag off" technique, it dries in about 1.5 hours at 25°C and 50% humidity. Using a 4-6mm roller on softwood takes around 2 hours, while hardwoods need about 2.5 hours to dry.

For coverage, undiluted stain covers approximately 10-14m<sup>2</sup> per litre on softwoods and 14-16m<sup>2</sup> per litre on hardwoods. When mixed as a tint with products like Monothane, Duothane, Tungseal, or Modified Oil, it covers about 10m<sup>2</sup> per litre.

