



Parquet Guide

Sanding solutions for flooring professionals 2024





Global presence

Sustainability

We are taking responsibility at Bosch, and making our over 400 locations carbon neutral in 2020. But that's not all: we want to shape climate action and also take a close look at the carbon footprint of our products, purchased goods, and logistics processes.





Offset CO₂ emissions



Procure green electricity



New Clean Power



Energy efficiency





Local expertise

Bosch Power Tools 18

the **Perfect Surface**in the most efficient and
effective way
possible.

About us
Belt series
6
Roll series
8
Disc series
10
Floor Pads series
14
Product list
16



Global partner

Developed and manufactured using Swiss technology and represented in over 80 countries: sia Abrasives markets complete abrasive systems for all kinds of surfaces with its ~1,300 employees worldwide.

World's most modern abrasives plant

Setting the pace for the next generations of abrasives: Innovative abrasives are manufactured "just in time" using a modularised production process in the highly innovative Maker 5 plant (picture above).







Your Key to a Perfect Surface

Visit us online:



www.sia-abrasives.com/



en-auwww.sia-abrasi2812



Industry Know-how

As a world-leading manufacturer of high-quality abrasives with more than 140 years of expertise and innovativeness, we know the process steps of our customers and offer the right sanding solution for any material.





















Types of abrasives

Over 60,000 abrasive products in a variety of abrasive formats, sizes and specifications for all materials, applications and requirements.



Coated abrasives

- Classical coated abrasives and abrasive systems.
- For advanced surface treatment of all types of material.



Nonwoven abrasives

- Nonwoven products for preparation and cleaning task-sand for structuring.



Foam abrasives

- Foam sanding pads in the widest possible range of shapes and grades.
- For precision treatment of wood, fillers, paints and lacquers.



sia Abrasives Product profile

2570 siabite - The ceramic belt with an appetite for high stock removal and an even scratch pattern 2560 siabite



-Fast and aggressive cut

-Even scratch pattern

-Longest lifetime

-Extreme stock removal rate

2570 siabite 2560 siabite

The hungry ceramic grit belt with razor sharp teeth for exceptional stock removal, yet leaving an even scratch pattern.

siabite - the one that bites!

Product profile

Grit type: Ceramic Grit range: 40-100

Backing: Y-wt cloth, cotton

Coating: Closed

Bonding: Resin over resin

Applications

- Coarse sanding in parquet and plywood manufacturing
- Structuring and final sanding
- Flush sanding of protrusions on cross-grained wood
- Surface finishing

2800 siaron - The allrounder for coarse to fine sanding applications



2800 siaron

The all-purpose 2800 siaron offers a wide range of uses in sanding and surface treatment of timber floors, delivering high stock removal, long life and excellent surface finishing results.

Product profile

Grit type: Zirconia alumina Grit range: 24-120 Backing: Y-wt cloth

Coating: Closed

Bonding: Resin over resin

Advantages

- May be used wet or dry
- Backing with very high stability
- Wide range of applications
- Excellent finish

Applications

- Sanding down
- Smoothing and blending
- Surface treatment
- Structuring and final sanding

2812 siaral x – The professional abrasive for edges, seams, solid wood and parquet flooring



2812 siaral x

As a specialist product for the surface treatment of hardwood, glued solid wood panels as well as for parquet flooring and plywood production, 2812 siaral x with its robust cloth backing produces top-quality results in floor sanding applications.

Product profile

Grit type: Mixed grit Grit range: 24-120

Backing: Y-wt cloth, cotton

X-wt cloth, cotton

Closed

Bonding: Resin over resin

Advantages

- Suitable for long periods of use thanks to very robust backing and optimised grit spreading technology
- Extremely high performance when preparing hardwood with coarser grit sizes combined with an application optimised belt joint

Applications

Coating:

- Flush sanding of protrusions on cross-grained wood
- Flatting of edges and rabbets
- Coarse sanding in parquet and plywood manufacturing

24-100

120

- Intermediate sanding of parquet flooring

2820 siamet - The all-round sanding belt for high stock removal paired with an excellent finish



2820 siamet

As a specialist product designed for dry sanding with high removal rates as well as excellent edge stability and tear resistance, 2820 siamet is suitable for a wide variety of jobs including timber floors.

Product profile

Grit type: Zirconia alumina Grit range: 36-120 Backing: Y-wt cloth

Coating: Closed

Bonding: Resin over resin

Advantages

- High edge stability, high initial tearing resistance
- Long lifetime
- High performance
- Aggressive cut

Applications

- Removal of paint
- Sanding down
- Surface finishing

sia Abrasives **Product profile**

1707 siapar - For maximum performance during heavy-duty sanding on wood, old paints, plasterboard and stone



1707 siapar

When it comes to removing underseal from wood, plasterboard, stone, concrete and old paints, 1707 siapar has what it takes. High performance and long life in heavy-duty applications.

Product profile

Silicon carbide Grit type: 24-36 Grit range:

Y-wt cloth, cotton Backing:

Bonding: Resin over resin

Applications

Coating:

- Keying of solid wood
- Sanding off of plaster, stone and concrete
- Sanding off of floor sealing, paints and old lacquer

Mechanical closed

- Keying of insulating boards

Advantages

- Low clogging
- Very high performance
- Long life in heavy-duty applications

1749 siaral f - The number 1 for intermediate and final laquer sanding



1749 siaral f

A specialist abrasive for keying MDF, HDF and chipboard, 1749 siaral f not only has a long lifetime, it also produces a high-quality surface finish.

Product profile

Silicon carbide Grit type: Grit range: 40-120 Backing: F-wt paper

Coating: Closed

Bonding: Resin over resin

Advantages

- Perfect surfaces thanks to TopTec
- Dust-free process: Antistatic construction minimises dust build-up on belt, workpiece and machinery
- Very good finish on solid wood and veneer

Applications

- Keying of solid wood
- Sanding off of plaster, stone and concreteSanding off of floor sealing, paints and old lacquer
- Keying of insulating boards

siaral x – The professional abrasive for edges, seams, solid wood and parquet flooring



2812 siaral x

As a specialist product for the surface treatment of hardwood, glued solid wood panels as well as for parquet flooring and plywood production, 2812 siaral x with its robust cloth backing produces top-quality results in floor sanding applications.

Product profile

Grit type: Mixed grit 24-100 Grit range:

Backing: Y-wt cloth, cotton

Coating: Closed

Bonding: Resin over resin

Advantages


- Suitable for long periods of use thanks to very robust backing and optimised grit spreading technology
- Extremely high performance when preparing hardwood with coarser grit sizes.

Applications

- Flush sanding of protrusions on cross-grained wood
- Flatting of edges and rabbets
- Coarse sanding in parquet and plywood manufacturing


24-100


- Intermediate sanding of parquet flooring.



Giving our coated abrasive product very specific grip and adhesion, stretch, tear resistance, tensile strength, flexibility and stability properties.

Only the best is good enough!





sia Abrasives Product profile

7500 sianet - The powerful net-backed abrasive



7500 sianet

The special net structure of 7500 sianet CER enables dust-free sanding with the highest abrasive performance — The ceramic abrasive grain provides the highest removal rate and longest lifetime.

Product profile

Grit type: Ceramic aluminium oxide Grit range: 80-400 Backing: Mesh

Coating: Mechanical

Bonding: Resin over resin

Advantages

- Full-surface dust extraction
- High removal rate without clogging
- High tear resistance, thanks to sturdy net backing
- High-performance product with ceramic aluminium oxide

Applications

- Sanding off old varnish, paints and stains
- Sanding off old paint and varnish
- Sanding off raised wooden fibres
- Sanding floorboards

2790 sianet - The powerful net-backed abrasive



2790 sianet

For keying solid wood, intermediate lacquer sanding, painting preparation and parquet sanding – 2790 sianet impresses with its low clogging and very fine finish and excellent surface quality in lacquering applications.

Product profile

Grit type: Silicon carbide Grit range: 60-220 Backing: Mesh

Coating: Mechanical

Bonding: Resin over resin

Advantages

- Low clogging
- Longest lifetime
- Machine sanding / intermediate sanding of the lacquer on surfaces
- Very fine finish

Applications

- Keying solid wood
- Sanding off raised wooden fibres
- Intermediate lacquer sanding

1815 siatop - For fast and cost effective surface treatment



1815 siatop

1815 siatop impresses with its high removal rate, long lifetime and very good finish in a wide range of applications

Product profile

Grit type: Zirconia alumina Grit range: 24-150 Backing: Fibre

F-wt paper Closed

Bonding: Resin over resin

Advantages

- Versatile all-round product with an attractive range of options
- Outstanding performance in dry sanding applications
- Fast and rugged stock removal with regular surface quality
- Cost reduction thanks to long lifetime

Applications

Coating:

- Sanding down
- Surface finishing
- Removal of lacquers
- Structuring and final sanding

7241 siacarbon - For finishing scratch-resistant surfaces



7241 siacarbon

Ideal for wet and dry machine sanding of hard surfaces: For unique results when keying scratch-resistant lacquers and composite materials with a minimum of abrasives consumption.

Product profile

Grit type: Diamond Grit range: 180-500 Backing: Cloth

Coating: Special process

Bonding: Resin over resin

Advantages

- Excellent performance on hard materials
- Extremely long lifetime thanks to state-of-the-art diamond technology
- Full-surface dust extraction
- Consistent removal rates

Applications

- Keying of scratch-resistant coating systems
- Fine finish sanding

P24-P40

P60-P150

sia Abrasives **Product profile**

1707 siapar - Maximum performance during heavy-duty sanding on wood, old paints and plasterboard



1707 siapar

When it comes to removing plasterboard, stone, concrete, old paints and under-seal from wood, 1707 siapar has what it takes. High performance and long life in heavy-duty applications.

Product profile

Silicon carbide Grit type: 16-36 Grit range:

Backing: Y-wt cloth, cotton

Bonding: Resin over resin

Applications

Coating:

- Keying of solid wood
- Sanding off of plaster, stone and concreteSanding off of floor sealing, paints and old lacquer

Mechanical closed

- Keying of insulating boards

Advantages

- Low clogging
- Very high performance
- Long life in heavy-duty applications

1749 siaral f - The number 1 for intermediate and final laquer sanding



1749 siaral f

A specialist abrasive for keying MDF, HDF and chipboard, 1749 siaral f not only has a long lifetime, it also produces a high-quality surface finish.

Product profile

Silicon carbide Grit type: Grit range: 40-400 F-wt paper Backing:

Coating: Closed

Bonding: Resin over resin

Advantages

- Perfect surfaces thanks to TopTec
- Dust-free process: Antistatic construction minimises dust build-up on belt, workpiece and machinery
- Very good finish on solid wood and veneer

Applications

- Keying of solid wood
- Sanding off of plaster, stone and concrete
- Sanding off of floor sealing, paints and old lacquer
- Keying of insulating boards

2812 siaral x – The professional abrasive for edges, seams, solid wood and parquet flooring



2812 siaral x

As a specialist product for the surface treatment of hardwood, glued solid wood panels as well as for parquet flooring and plywood production, 2812 siaral x with its robust cloth backing produces top-quality results in floor sanding applications.

Product profile

Grit type: Mixed grit Grit range: 24-120

Backing: Y-wt cloth, cotton

X-wt cloth, cotton P120

P24-P100

Coating: Closed

Resin over resin Bonding:

Advantages

- Suitable for long periods of use thanks to very robust backing and optimised grit spreading technology
- Extremely high performance when preparing hardwood with coarser grit sizes.

Applications

- Flush sanding of protrusions on cross-grained wood
- Flatting of edges and rabbets
- Coarse sanding in parquet and plywood manufacturing
- Intermediate sanding of parguet flooring

6120 siafleece - For even surface finishes in manual and portable machine sanding



6120 siafleece

6120 siafleece can be used for dry and wet sanding and impresses due to its high conformability, consistent performance over the entire lifetime, low tendency to clog, and consistently high surface quality.

Product profile

Aluminium oxide Grit type: Grit range: Very fine A Nonwoven Backing: Coating: Mechanical

Bonding: Resin over resin

Advantages

- Highly flexible and adaptable to contours
- For manual or portable machine sanding
- Low clogging
- Suitable for general use in dry and wet sanding applications

Applications

- Sanding off raised wooden fibres
- Keying surfaces for better paint adhesion
- Sanding off old varnish, paints and stains
- Fine sanding of surfaces



sia Abrasives Product profile

F/Pad Black - For heavy-duty wet stripping



Our most popular stripping pad designed for heavy-duty wet stripping. Very aggressive texture to remove wax, dirt and any finish. Tough, durable and built to perform.

F/Pad Brown - For wet or dry stripping




A very strong pad for wet or dry stripping applications. Quickly removes wax, dirt and old finish leaving surface ready for immediate recoating.

F/Pad Green - For wet scrubbing or light stripping



Our toughest duty, most aggressive scrubbing pad for heavily soiled areas. Best when used for wet scrubbing or light stripping. Very durable and long-lasting.

F/Pad Red - For dry or spray buffing



Restores gloss while removing scuff marks and dirt on medium traffic areas. Can be used dry or spray buffing to produce a sparkling shine.

F/Pad Black - For dry buffing or light cleaning



The perfect pad for light cleaning and dry buffing. Removes scuffs and black heel marks while producing a high gloss shine.

F/Pad Black - For polishing soft waves on wood floors



This popular extra fine pad is formulated for polishing clean, dry floors. A fine water mist is used to produce a high gloss wet look.

F/Pad Blue - For wet scrubbing or medium-duty spray cleaning



Removes heavy dirt and scuff marks on most floor surfaces. This pad will remove the top layer of floor finish.

A B R A S I V E S

sia Abrasives 407mm Floor Pads




...Not just known for high quality belts and discs!

- ☐ Available in various grit ranges to suit multiple different applications.
- ☐ Suitable for stripping, scrubbing, cleaning, buffing and polishing.
- ☐ Removable centre hole piece.













Series	Dimensions	Grit range
1707 siapar Silicon carbide	203mm x 25000mm 254mm x 25000mm 305mm x 25000mm	P20 - P36 P24 P24 - P36
1749 siaral f Silicon carbide	203mm x 50000mm 254mm x 50000mm 305mm x 50000mm 405mm x 50000mm	P40 - P120 P40 - P120 P40 - P120 P80 - P100
2812 siaral x Mixed grit	203mm x 25000mm 305mm x 25000mm	P24 - P80 P24 - P100



Series	Diameter	Colours
Floor Pads	407mm	Black, brown, green, blue, red, tan, white



Series	Diamotor	Description	Crit rango
Series	Diameter	Description	Grit range
1707 siapar Silicon carbide	150mm 178mm 178mm 178mm 407mm 407mm	siafast siafast CH 22mm Star CH A 22mm No hole CH D/Sided 25mm	P24 P24 P24 P16 - P36 P16 - P24 P16 - P24
1749 siaral f Silicon carbide	125mm 150mm 178mm 178mm 178mm 200mm 407mm	siafast siafast siafast CH 22mm Star CH A 22mm siafast No hole CH D/Sided 25mm	P60 - P400 P40 - P150 P40 - P120 P40 - P120 P40 - P120 P40 - P150 P40 - P240 P40 - P120
1815 siatop Zirconia alumina	150mm 180mm 407mm	No hole, 6 & 8 hole No hole No hole	P24 - P150 P24 - P120 P24 - P150
2790 sianet Silicon carbide	407mm	Mesh Full-surface dust extraction	P60 - P220
2812 siaral x Mixed grit	178mm	Star CH A 22mm siafast	P36 - P80 P24 - P120
6120 siafleece Aluminium Oxide	407mm	Nonwoven siafast Full-surface extraction	Very fine A
7241 siacarbon Diamond	150mm	Cloth siafast Full-surface extraction	P180 - P500
7500 sianet Ceramic aluminium oxide	150mm 407mm	Mesh Full-surface extraction	P80 - P400 P80 - P180
1950 siaspeed Aluminium Oxide	125mm 150mm	Multiple hole patterns including 49H siafast	P40 - P1500





¹ With online registration
www.bosch-professional.com/guarante

	www.bosch-professional.com/guarantee		
	Description	Part Number	Product Information
	GOP 18V-28	06018B6001	18.0V Multi Tool, Brushless Motor, STARLOCK PLUS, 8000-20,000rpm, Variable speed, Soft grip housing, 2.8° Oscillation, SDS Snap In, LED Light, 1.6kg
9	GOP 12V-28	06018B5001	12.0V Multi Tool, Brushless Motor, STARLOCK PLUS, 5000-20,000rpm, Variable speed, Soft grip housing, 1.4° Oscillation, SDS Snap In, 1.2kg
B man land	GOP 30-28	0601237040	Corded Multi Tool, Brushless Motor, STARLOCK PLUS, 8000-20,000rpm, Variable speed, Soft grip housing, 1.4° oscillation, 1.5kg
	GST 18V-125 B	06015B0041	18.0V Jigsaw Barrel Grip 125mm Cutting Depth 550-2700spm, LED Light (on/off) DC Brushless Motor Type SDS Snap In, 2.5kg
	GST 12V-70	06015A1040	12.0V Jigsaw Barrel Grip 70mm Cutting Depth 1,500 – 2,800 spm, LED Light (on/off) SDS Snap In, 1.7kg
	GSB 18V-60 C	0615990J9U	18.0V Brushless Drill Driver Drill, 150Nm Torque 28,500 bpm, Max. drilling diameter in wood 38 mm Max. drilling diameter in steel 13 mm
	GDX 18V-210 C	06169J0200	18V Impact Driver/Wrench, Tool holder 1/4" Hex Uni, 1/2" Square, 210Nm, 0-3400rpm, 0-4100bpm, M6-M16, 1.2kg













	Description	Part Number	Product Information
	GSS 18V-13	06019L0140	18.0 V Cordless Orbital Sander Hook & loop fastening 1.6mm orbit diameter 6,000-10,000rpm Delta sanding plate included, 1.6 kg
	GSS 12V-13	06019L0040	12.0 V Cordless Orbital Sander Hook & loop fastening 1.6mm orbit diameter 6,000-10,000rpm Delta sanding plate included, 1 kg
201	GEX 18V-125	0601372241	18.0 V 125mm Random Orbital Sander Hook & loop fastening 2.5mm orbit diameter 6,000-10,000rpm 1.6 kg
	GEX 12V-125	0601372141	12.0 V 125mm Random Orbital Sander Hook & loop fastening 2.5mm orbit diameter 6,000-10,000rpm 1.1 kg
8	GEX 40-150	060137B240	Corded 150mm Random Orbital Sander Hook & loop fastening 4mm orbital diameter 5,500 - 12,000rpm 2.4kg
	GET 75-150	0601257141	Corded 150mm Random Orbital Sander Hook & loop fastening 4.5mm orbital diameter 3,300 - 7,300rpm

2.6kg









Your Key to a Perfect Surface

Contact our friendly customer service team:
Australia 1300 SIA 123 Get social with us!
New Zealand 0800 SIA 123 IG: @siaabrasives
or speak to your nearest sia Abrasives distributor Fb: sia Abrasives ANZ - Floor



